

Configuratie standard

- disponibile in variante: PS125™ (fara imprimanta) sau PS125 OneStep™ (cu imprimanta).
- cote reduse de gabarit (56 x 48 cm).
- masa-suport portabila pentru alimentarea ergonomica si rapida cu pungi Autobag pre-deschise la rola.
- display reglare/ control prietenos, panou electronic-display luminos si un meniu de navigare simplu
- stocheaza pana la 10 job-uri diferite de ambalare ce pot fi accesate/ rulate oricand ulterior
- sigileaza automat pungi si contorizarea pachetelor rezultate. Comanda de sigilare automata Push-to Seal™ sau actionarea de la pedala de picior
- dispozitiv Auto Thread™ pentru o facila schimbare a rozelor de pungi

- suport reglabil de fixare a rolei cu pungi
- ghidajul pungilor asigura pozitionarea exacta a pungii in vederea imprimarii*, alimentarii si lipirii

Optiuni

- aerator pungi
- palnii de alimentare
- chit de baza – piese de schimb

Dotari mecanice



Masa – suport rabatabila ce asigura acces usor la rola de pungi. Dispozitivul AutoThread™ usureaza manevrarea la schimbarea rozelor.



Zona de incarcare deschisa si bara mobile de sigilare imbunatatesc flexibilitatea in alimentare si cresc siguranta in utilizare

Parametrii tehnici:

	PS 125
Greutate:	37 kg
Partea electrica:	110/220 V CA, 50/60 Hz: 4.0 A
Zona incarcare:	pana la 86 mm
Grosime pungi:	35 - 100 my
Marime pungi:	lat.: 50 - 250 mm lungime 100 - 430 mm
Greutate max. bun de ambalat:	1.1 kg



	PS 125 OneStep
Greutate:	50 kg
Partea electrica:	110/220 V CA, 50/60 Hz: 4.0 A
Zona incarcare:	pana la 86 mm
Grosime pungi:	35 - 100 my
Marime pungi:	lat.: 50 - 250 mm lungime 100 - 430 mm
Greutate max. bun de ambalat:	1.1 kg

